

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

SECTION 1: Identification

Product Identifier

Product Name: Thick and Foamy

Product code: DT-150

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: High Foaming Detergent

Uses Advised Against: NA

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer: **United States**

JBS Industries 2726 Henkle Drive Lebanon, Ohio 45036 513-228-2800 SBAETEN@JBSINDUSTRIES.COM

Emergency Telephone Number:

North America

CHEMTREC 800-424-9300 (24 hours)

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin corrosion, category 1A Serious eye damage, category 1 Carcinogenicity, category 1A Reproductive toxicity, category 1B

Label elements

Hazard Pictograms:





Signal Word: Danger **Hazard statements:**

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H350 May cause cancer

H360 May damage fertility or the unborn child.

Precautionary Statements:

Page 1 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P264 Wash Contaminated area thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P202 Do not handle until all safety precautions have been read and understood

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 Wash contaminated clothing before reuse

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P310 Immediately call a POISON CENTER/doctor if difficulty in breathing occurs.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P405 Store locked up

P501 It is the responsibility of the waste generator to characterize all waste materials according to applicable regulatory entities.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 68584-22-5	Benzenesulfonic acid, C10-16-alkyl derivatives	1-96
CAS Number: 1310-73-2	Sodium hydroxide	1-45
CAS Number: 9004-82-4	2-dodecoxyethyl hydrogen sulfate	1-10
CAS Number: 68603-42-9	Amides, coco, N,N-bis(hydroxyethyl)	1-10
CAS Number: 1300-72-7	Sodium Xylenesulfonate	1-10
CAS Number: 68131-39-5	Alcohols, C12-15, ethoxylated	<5
CAS Number: 75-21-8	Ethylene oxide	<0.036
CAS Number: 123-91-1	1,4-dioxane	<0.036

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Not determined or not applicable.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If

Page 2 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

experiencing respiratory symptoms, seek medical advice/attention.

After Skin Contact:

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

After Eye Contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Exposure may cause cancer. Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

In case of skin contact, seek prompt medical attention while rinsing is continued.

In case of ingestion, seek prompt medical attention.

Notes for the Doctor:

Not determined or not applicable.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA)

Page 3 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

with a full-face piece operated in positive pressure mode.

Special precautions:

Not determined or not applicable.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Ident	ifier	Permissible concentration
ACGIH	Sodium hydroxide	1310-	73-2	Ceiling Limit: 2 mg/m³
	Ethylene oxide	75-21	-8	8-Hour TWA: 1 ppm
	1,4-dioxane	123-9	1-1	8-Hour TWA: 20 ppm
OSHA	Sodium hydroxide	1310-	73-2	8-Hour TWA-PEL: 2 mg/m ³
	Ethylene oxide	75-21	-8	8-Hour TWA-PEL: 1 ppm
	Ethylene oxide	75-21	-8	15-Minute STEL: 5 ppm
	Ethylene oxide	75-21	-8	8-Hour TWA: 0.5 ppm (Action level)

Page 4 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019 Pa

Revision date: 05.18.2023

Thick and Foamy

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	1,4-dioxane	123-91-1	8-Hour TWA-PEL: 360 mg/m ³ (100 ppm)
NIOSH	Sodium hydroxide	1310-73-2	IDLH: 10 mg/m³
	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m³
	Ethylene oxide	75-21-8	IDLH: 800 ppm
	Ethylene oxide	75-21-8	Ceiling Limit: 9 mg/m³ (5 ppm [10-min/day])
	Ethylene oxide	75-21-8	REL-TWA: 0.18 mg/m³ (0.1 ppm [up to 10 hr])
	1,4-dioxane	123-91-1	IDLH: 500 ppm
	1,4-dioxane	123-91-1	Ceiling Limit: 3.6 mg/m³ (1 ppm [30-min])
United States(California)	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m³
	Sodium hydroxide	1310-73-2	REL: 8 ug/m³ (Acute Inhalation)
	Ethylene oxide	75-21-8	15-Minute STEL: 5 ppm
	Ethylene oxide	75-21-8	8-Hour TWA-PEL: 2 mg/m³ (1 ppm)
	Ethylene oxide	75-21-8	8-Hour TWA: 0.5 ppm (Action level)
	1,4-dioxane	123-91-1	8-Hour TWA-PEL: 1 mg/m ³ (0.28 ppm)

Biological Limit Values:

ziologicai ziniic valaco.						
Country (Legal Basis)	Substance	Identifi er	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	Ethylene oxide	75-21-8	N-(2- hydroxyethyl)- valine (HEV) hemoglobin adducts	Hemoglobin adducts	Not critical	5000 pmol/g
	Ethylene oxide	75-21-8	S-(2- hydroxyethyl) mercapturic acid (HEMA)	Creatinine in urine	End of shift	5 μg/g

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eve and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used

Page 5 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Liquid
Odor	Std.
Odor threshold	Not determined or not available.
рН	7
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Page 6 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

None known.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Benzenesulfonic acid, C10-16-	inhalation	LC50 Rat: >1.9 mg/L (4 h [aerosol])
alkyl derivatives	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg
2-dodecoxyethyl hydrogen sulfate	oral	LD50 Rat: 1600 mg/kg
Alcohols, C12-15, ethoxylated	oral	LD50 Rat: > 2000 mg/kg
Sodium hydroxide	oral	LD50 Rat: 140-340 mg/kg
	dermal	LD50 Rabbit: 1350 mg/kg
Amides, coco, N,N- bis(hydroxyethyl)	oral	LD50 Rat: 4100 mg/kg
Sodium Xylenesulfonate	dermal	LD50 Rabbit: >= 2000 mg/kg
	oral	LD50 Rat: >= 3346 mg/kg
Ethylene oxide	Inhalation ATE	LC50 Rat: 700 ppmV (4 hr (Gas))
	Oral ATE	LD50 Rat: 100 mg/kg
1,4-dioxane	oral	LD50 Rat: 5150 mg/kg
	dermal	LD50 Rabbit: 7600 mg/kg
	inhalation	LC50 Rat: 9158 ppmV (4 hr - Vapor)

Skin Corrosion/Irritation

Assessment:

Causes severe skin burns and eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Sodium hydroxide	Causes severe skin burns.

Page 7 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

Name	Result
2-dodecoxyethyl hydrogen sulfate	Causes skin irritation.
Amides, coco, N,N- bis(hydroxyethyl)	Causes skin irritation.
Benzenesulfonic acid, C10-16-alkyl derivatives	Causes severe skins burns.
Alcohols, C12-15, ethoxylated	Causes skin irritation.
Ethylene oxide	Causes severe skin burns.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Sodium hydroxide	Causes serious eye damage.
2-dodecoxyethyl hydrogen sulfate	Causes serious eye irritation.
Amides, coco, N,N- bis(hydroxyethyl)	Causes serious eye damage.
Sodium Xylenesulfonate	Causes serious eye irritation.
Benzenesulfonic acid, C10-16-alkyl derivatives	Causes serious eye damage.
Alcohols, C12-15, ethoxylated	Causes serious eye damage.
Ethylene oxide	Causes serious eye damage.
1,4-dioxane	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Carcinogenicity
Assessment:

May cause cancer.

Product Data: No data available.

Substance Data:

Name	Species	Result
Ethylene oxide		May cause cancer.

Page 8 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

Name	Species	Result
1,4-dioxane		May cause cancer. 1,4-dioxane is characterized as "likely to be carcinogenic to humans." This characterization is based on the following findings: (1) inadequate evidence of carcinogenicity in humans, and (2) sufficient evidence in animals (i.e., hepatic tumors in multiple species [three strains of rats, two strains of mouse, and in guinea pigs] mesotheliomas of the peritoneum, mammary, and nasal tumors have also been observed in rats following 2 years of oral exposure to 1,4- dioxane). U.S. Environmental Protection Agency's Integrated Risk Information System (IRIS).

International Agency for Research on Cancer (IARC):

Name	Classification
2-dodecoxyethyl hydrogen sulfate	Not Applicable
Alcohols, C12-15, ethoxylated	Not Applicable
Amides, coco, N,N- bis(hydroxyethyl)	Group 2B
Sodium hydroxide	Not Applicable
Sodium Xylenesulfonate	Not Applicable
Benzenesulfonic acid, C10-16-alkyl derivatives	Not Applicable
Ethylene oxide	Group 1
1,4-dioxane	Group 2B

National Toxicology Program (NTP):

Name	Classification
2-dodecoxyethyl hydrogen sulfate	Not Applicable
Amides, coco, N,N- bis(hydroxyethyl)	Not Applicable
Sodium hydroxide	Not Applicable
Alcohols, C12-15, ethoxylated	Not Applicable
Sodium Xylenesulfonate	Not Applicable
Benzenesulfonic acid, C10-16-alkyl derivatives	Not Applicable
Ethylene oxide	Known to be human carcinogens
1,4-dioxane	Reasonably anticipated to be human carcinogens

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available. **Substance Data:**

Name	Result
Ethylene oxide	May cause genetic defects.

Page 9 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

Reproductive Toxicity

Assessment:

May damage fertility or the unborn child.

Product Data:

No data available.

Substance Data:

Name	Result
Ethylene oxide	May damage fertility. Suspected of damaging the unborn child.

Specific Target Organ Toxicity (Single Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available. **Substance Data:**

Name	Result
Ethylene oxide	May cause respiratory irritation.
	May cause drowsiness or dizziness.
1,4-dioxane	May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available. Substance Data:

Name	Result
Ethylene oxide	Studies on the effects of Ethylene oxide have concluded not only neurotoxic symptoms in humans, but also measured effects on nerve conduction velocities indicative of sensorimotor neuropathy, and axonal degeneration observed in nerve biopsies of exposed workers.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available. **Other Information:**

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Page 10 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

Name	Result
Alcohols, C12-15, ethoxylated	Aquatic Invertebrates EC50 Acartia tonsa: 0.88 mg/L (48 hr [mortality])
	Aquatic Plants EC50 Raphidocelis subcapitata: 0.031 mg/L (72 hr [growth rate])
	Fish LC50 Pimephales promelas: 0.628 mg/L (96 hr, QSAR)
Sodium hydroxide	Fish LC50 Gambusia affinis: 125 mg/L (96 hr)
	Aquatic Invertebrates EC50 Ceriodaphnia sp.: 40.4 mg/L (48 hr [immobilization])
Sodium Xylenesulfonate	Aquatic Plants EC50 Selenastrum capricornutum: >=758 mg/L (96 hr [growth rate; read-across])
	Fish LC50 Oncorhynchus mykiss: >=1580 mg/L (96 hr [read-across])
	Aquatic Invertebrates EC50 Daphnia magna: >1020 mg/L (48 hr [mobility; read-across])
Ethylene oxide	Aquatic Plants EC50 Pseudokirchneriella subcapitata: 240 mg/L (96 h, read-across substance data)
	Aquatic Invertebrates LC50 Daphnia magna: 212 mg/L (48 h)
	Fish LC50 Pimephales promelas: 84 mg/L (96 h)
1,4-dioxane	Fish LC50 Pimephales promelas: 9850 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >1000 mg/L (48 hr)
	Aquatic Plants EC50 Pseudokirchneriella subcapitata: >1000 mg/L (72 hr)

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Alcohols, C12-15, ethoxylated	Aquatic Invertebrates NOEC Daphnia magna: 0.036 mg/L (21 d [mortality])
1,4-dioxane	Fish NOEC Pimephales promelas: 145 mg/L (32 d)
	Aquatic Invertebrates NOEC Daphnia magna: 1000 mg/L (21 d)

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Benzenesulfonic acid, C10-16-alkyl derivatives	Under test conditions no biodegradation observed.
Sodium hydroxide	Persistence and degradability studies do not apply to inorganic substances.
Alcohols, C12-15, ethoxylated	This substance is readily biodegradable. $> 60 - \le 100\%$ degradation in water, after 28 days.
Sodium Xylenesulfonate	The substance is readily biodegradable. 83 - 85% degradation, measured by CO2 evolution, after 28 days.
Ethylene oxide	Readily biodegradable (96% degradation after 28 days, measured by TOC removal).
1,4-dioxane	Not readily biodegradable (< 10 % degradation after 29 days, measured by CO2 evolution).

Bioaccumulative Potential

Page 11 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

Product Data: No data available.

Substance Data:

Name	Result
Sodium hydroxide	Bioaccumulation is not expected based on the substance's high water solubility. In addition, sodium is a naturally-occurring element that is prevalent in the environment and to which organisms are exposed regularly, for which they have some capacity to regulate the concentration in the organism.
Alcohols, C12-15, ethoxylated	This substance has the potential to bioaccumulate significantly (log Pow=5.79).
Amides, coco, N,N- bis(hydroxyethyl)	This substance is not expected to bioaccumulate (log Kow=2.89).
Ethylene oxide	Low potential for bioaccumulation (logKow = -0.3).
1,4-dioxane	Does not accumulate in aquatic organisms (mean BCF: 0.45).

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Sodium hydroxide	The substance has a high water solubility. As the dilution of the substance increases, its speed of movement through soil increases. During movement through soil, some ion exchange will occur.
Alcohols, C12-15, ethoxylated	This substance is moderately to hardly mobile therefore, adsorption to soil is expected ((log Koc=2.301 to 3.352 (MCI method) and log Koc=3.7 to 4.8 (Van Compernolle et al. (2006) method.))
Amides, coco, N,N- bis(hydroxyethyl)	This substance is mobile, therefore adsorption to soil is not expected (log Koc= 1.60).
1,4-dioxane	Significant adsorption to solid soil phase is not expected (calculated log Koc: 0.51 at 25 °C).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Alcohols, C12-15, ethoxylated	This substance is not PBT.
Sodium hydroxide	PBT assessment does not apply to inorganic substances.
Sodium Xylenesulfonate	The substance is not PBT.
Ethylene oxide	This substance is not PBT.
1,4-dioxane	Under assessment as Persistent, Bioaccumulative and Toxic (PBT list).

vPvB assessment:

Alcohols, C12-15, ethoxylated	This substance is not vPvB.
Sodium hydroxide	vPvB assessment does not apply to inorganic substances.
Sodium Xylenesulfonate	The substance is not vPvB.
Ethylene oxide	This substance is not vPvB.
1,4-dioxane	This substance is not vPvB.

Other Adverse Effects: No data available.

Page 12 of 15

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Page 13 of 15

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

Thick and Foamy

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	Not Regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed. **Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances:

75-21-8 Ethylene oxide	Listed
------------------------	--------

SARA Section 313 Toxic Chemicals:

	75-21-8	Ethylene oxide	Listed
--	---------	----------------	--------

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019 Page 14 of 15

Revision date: 05.18.2023

Thick

on date: 05.18.202	<u>'</u>		
and Foamy			
123-91-1	1,4-dioxane		Listed
CERCLA:			•
1310-73-2	Sodium hydroxide	Listed	1000 lb
75-21-8	Ethylene oxide	Listed	10 lbs
123-91-1	1,4-dioxane	Listed	100 lbs
RCRA:		•	
75-21-8	Ethylene oxide	Listed	U115
123-91-1	1,4-dioxane	Listed	U108
Section 112(r) of	the Clean Air Act (CAA):	•	
75-21-8	Ethylene oxide		Listed
Massachusetts Ri	ght to Know:		
1310-73-2	Sodium hydroxide		Listed
75-21-8	Ethylene oxide		Listed
123-91-1	1,4-dioxane		Listed
lew Jersey Right	to Know:		
1310-73-2	Sodium hydroxide		Listed
75-21-8	Ethylene oxide		Listed
123-91-1	1,4-dioxane		Listed
New York Right to	o Know:		
1310-73-2	Sodium hydroxide		Listed
75-21-8	Ethylene oxide		Listed
123-91-1	1,4-dioxane		Listed
Pennsylvania Rig	ht to Know:		
1310-73-2	Sodium hydroxide		Listed
75 21 0	Eu l'I		

1310-73-2	Sodium hydroxide	Listed
75-21-8	Ethylene oxide	Listed
123-91-1	1,4-dioxane	Listed

California Proposition 65:

△WARNING: This product can expose you to chemicals including Amides, coco, N,N-bis(hydroxyethyl), Diethanolamine, Strong inorganic acid mists containing sulfuric acid and 1,4-dioxane; which are known to the State of California to cause cancer; and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. ▲WARNING: This product can expose you to Ethylene oxide; which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 06.20.2019 Page 15 of 15

Revision date: 05.18.2023

Thick and Foamy

specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0 **HMIS:** 0-0-0

Initial Preparation Date: 06.20.2019

Revision date: 05.18.2023

End of Safety Data Sheet